



## Lift Table Specifications

### “L” Series Lift Tables 2,500 lb. Capacity

Vertical Travel	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Maximum Height	Up Travel Speed*
24”	7”	24” x 36”	48” x 60”	31”	6.3 sec.
36”	7”	24” x 48”	48” x 72”	43”	10 sec.
48”	7”	24” x 64”	48” x 96”	55”	11.3 sec.

### “L” Series Lift Tables 4,000 - 6,000 lb. Capacity

Vertical Travel	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Maximum Height	Up Travel Speed*
24”	7”	24” x 36”	48” x 60”	31”	12.5 sec.
36”	7”	24” x 48”	48” x 72”	43”	20 sec.
48”	7”	24” x 64”	48” x 96”	55”	22.5 sec.

### “L” Series Lift Tables 8,000 - 10,000 lb. Capacity

Vertical Travel	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Maximum Height	Up Travel Speed*
24”	10”	30” x 48”	54” x 78”	34”	17.5 sec.
36”	10”	30” x 60”	54” x 90”	46”	25 sec.
48”	10”	30” x 68”	54” x 98”	58”	35 sec.
60”	10”	30” x 84”	54” x 114”	70”	60 sec.

### “L” Series Lift Tables 12,000 lb. Capacity

Vertical Travel	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Maximum Height	Up Travel Speed*
24”	10”	30” x 48”	54” x 78”	34”	26 sec.
36”	10”	30” x 60”	54” x 90”	46”	37.5 sec.
48”	10”	30” x 68”	54” x 98”	58”	52.5 sec.
60”	10”	30” x 84”	54” x 114”	70”	60 sec.

\*Travel Speeds are based on units with a standard 2 HP motor.

#### Standard Features:

- 2 HP, three phase motor, 230/460 volt (Optional 5 HP, 230/460 volt OR 1 HP, 120 volt )
- Control voltage, 120 volt AC
- Hand held pendant, push button control. (Optional foot pedal control)
- DU bearing, lubricated for life.
- Turned, ground, polished and hard chromed axel pins
- Captured upper and lower rollers to prevent upending.
- Engineered and built in accordance with ANSI MH 29.1
- Internal power packs except 24” vertical travel units.
- External power packs on all 8,000 – 12,000 lb. units.

**\*\*Consult factory for non-standard sizes\*\***



## Lift Table Specifications

### “EW” Extra Wide Series Lift Tables 2,500 lb. Capacity

Vertical Travel	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Maximum Height	Up Travel Speed*
24”	7”	48” x 36”	72” x 60”	31”	6.3 sec.
36”	7”	48” x 48”	72” x 72”	43”	10 sec.
48”	7”	48” x 64”	72” x 96”	55”	11.3 sec.

### “EW” Extra Wide Series Lift Tables 4,000 - 6,000 lb. Capacity

Vertical Travel	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Maximum Height	Up Travel Speed*
24”	7”	48” x 36”	72” x 60”	31”	12.5 sec.
36”	7”	48” x 48”	72” x 72”	43”	20 sec.
48”	7”	48” x 64”	72” x 96”	55”	22.5 sec.

### “EW” Extra Wide Series Lift Tables 8,000 - 10,000 lb. Capacity

Vertical Travel	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Maximum Height	Up Travel Speed*
24”	10”	60” x 48”	84” x 78”	34”	17.5 sec.
36”	10”	60” x 60”	84” x 90”	46”	25 sec.
48”	10”	60” x 68”	84” x 98”	58”	35 sec.
60”	10”	60” x 84”	84” x 114”	70”	60 sec.

### “EW” Extra Wide Series Lift Tables 12,000 lb. Capacity

Vertical Travel	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Maximum Height	Up Travel Speed*
24”	10”	60” x 48”	84” x 78”	34”	26 sec.
36”	10”	60” x 60”	84” x 90”	46”	37.5 sec.
48”	10”	60” x 68”	84” x 98”	58”	52.5 sec.
60”	10”	60” x 84”	84” x 114”	70”	60 sec.

\*Travel Speeds are based on units with a standard 2 HP motor.

#### Standard Features:

- 2 HP, three phase motor, 230/460 volt (Optional 5 HP, 230/460 volt OR 1 HP, 120 volt )
- Control voltage, 120 volt AC
- Hand held pendant, push button control. (Optional foot pedal control)
- DU bearing, lubricated for life.
- Turned, ground, polished and hard chromed axel pins
- Captured upper and lower rollers to prevent upending.
- Engineered and built in accordance with ANSI MH 29.1
- Internal power packs except 24” vertical travel units.
- External power packs on all 8,000 – 12,000 lb. units.

**\*\*Consult factory for non-standard sizes\*\***



## Lift Table Specifications

### “T” Series Tilt Tables 2,500 lb. Capacity

Degree of Tilt	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Retaining Wall Height	Tilt Speed*
30°	10”	24” x 36”	60” x 60”	8”	7.5 sec.
45°	10”	24” x 36”	60” x 60”	8”	11.3 sec.
60°	10”	24” x 36”	60” x 60”	8”	15 sec.

### “T” Series Tilt Tables 4,000 - 6,000 lb. Capacity

Degree of Tilt	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Retaining Wall Height	Tilt Speed*
30°	10”	24” x 36”	60” x 60”	8”	7.5 sec.
45°	10”	24” x 36”	60” x 60”	8”	11.3 sec.
60°	10”	24” x 36”	60” x 60”	8”	15 sec.

\*Tilt Speeds are based on units with a standard 2 HP motor.

### “UE” Series Up-Ender 90° Tables 2,500 – 6,000 lb. Capacity

Capacity	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Retaining Wall Height	Tilt Speed*
2,500	12”	48” x 60”	60” x 72”	18” – 60”	20 sec.
4,000	12”	48” x 60”	60” x 72”	18” – 60”	20 sec.
6,000	12”	48” x 60”	60” x 72”	18” – 60”	20 sec.

### “UE” Series Up-Ender 90° Tables 8,000 – 10,000 lb. Capacity

Capacity	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Retaining Wall Height	Tilt Speed*
8,000	14”	48” x 60”	60” x 72”	18” – 60”	22 sec.
10,000	14”	48” x 60”	60” x 72”	18” – 60”	22 sec.

#### Standard Features:

- 2 HP, three phase motor, 230/460 volt (Optional 5 HP, 230/460 volt OR 1 HP, 120 volt )
- Control voltage, 120 volt AC
- Hand held pendant, push button control. (Optional foot pedal control)
- DU bearing, lubricated for life.
- Turned, ground, polished and hard chromed axel pins
- Captured upper and lower rollers to prevent upending.
- Engineered and built in accordance with ANSI MH 29.1

**\*\*Consult factory for non-standard sizes\*\***



## Lift Table Specifications

### “LT” Series Lift & Tilt Tables 2,000 lb. Capacity, 30° Tilt

Vertical Travel	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Maximum Height	Up Travel Speed*	Tilt Speed*
24”	15”	24” x 36”	48” x 60”	39”	6.3 sec.	7.5 sec.
36”	15”	24” x 48”	48” x 60”	51”	10 sec.	7.5 sec.
48”	15”	24” x 64”	48” x 64”	63”	11.3 sec.	7.5 sec.

### “LT” Series Lift & Tilt Tables 3,500 lb. Capacity, 30° Tilt

Vertical Travel	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Maximum Height	Up Travel Speed*	Tilt Speed*
24”	15”	24” x 36”	48” x 60”	39”	12.5 sec.	7.5 sec.
36”	15”	24” x 48”	48” x 60”	51”	20 sec.	7.5 sec.
48”	15”	24” x 64”	48” x 64”	63”	22.5 sec.	7.5 sec.

### “LT” Series Lift & Tilt Tables 5,500 lb. Capacity, 30° Tilt

Vertical Travel	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Maximum Height	Up Travel Speed*	Tilt Speed*
24”	15”	24” x 36”	48” x 60”	39”	12.5 sec.	7.5 sec.
36”	15”	24” x 48”	48” x 60”	51”	20 sec.	7.5 sec.
48”	15”	24” x 64”	48” x 64”	63”	22.5 sec.	7.5 sec.

### “LT” Series Lift & Tilt Tables 2,000 lb. Capacity, 45° Tilt

Vertical Travel	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Maximum Height	Up Travel Speed*	Tilt Speed*
24”	15”	24” x 36”	48” x 60”	39”	6.3 sec.	11.3 sec.
36”	15”	24” x 48”	48” x 60”	51”	10 sec.	11.3 sec.
48”	15”	24” x 64”	48” x 64”	63”	11.3 sec.	11.3 sec.

### “LT” Series Lift & Tilt Tables 3,500 lb. Capacity, 45° Tilt

Vertical Travel	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Maximum Height	Up Travel Speed*	Tilt Speed*
24”	15”	24” x 36”	48” x 60”	39”	12.5 sec.	11.3 sec.
36”	15”	24” x 48”	48” x 60”	51”	20 sec.	11.3 sec.
48”	15”	24” x 64”	48” x 64”	63”	22.5 sec.	11.3 sec.

### “LT” Series Lift & Tilt Tables 5,500 lb. Capacity, 45° Tilt

Vertical Travel	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Maximum Height	Up Travel Speed*	Tilt Speed*
24”	15”	24” x 36”	48” x 60”	39”	12.5 sec.	11.3 sec.
36”	15”	24” x 48”	48” x 60”	51”	20 sec.	11.3 sec.
48”	15”	24” x 64”	48” x 64”	63”	22.5 sec.	11.3 sec.



## Lift Table Specifications

### “LT” Series Lift & Tilt Tables 2,000 lb. Capacity, 60° Tilt

Vertical Travel	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Maximum Height	Up Travel Speed*	Tilt Speed*
24”	15”	24” x 36”	48” x 60”	39”	6.3 sec.	15 sec.
36”	15”	24” x 48”	48” x 60”	51”	10 sec.	15 sec.
48”	15”	24” x 64”	48” x 64”	63”	11.3 sec.	15 sec.

### “LT” Series Lift & Tilt Tables 3,500 lb. Capacity, 60° Tilt

Vertical Travel	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Maximum Height	Up Travel Speed*	Tilt Speed*
24”	15”	24” x 36”	48” x 60”	39”	12.5 sec.	15 sec.
36”	15”	24” x 48”	48” x 60”	51”	20 sec.	15 sec.
48”	15”	24” x 64”	48” x 64”	63”	22.5 sec.	15 sec.

### “LT” Series Lift & Tilt Tables 5,500 lb. Capacity, 60° Tilt

Vertical Travel	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Maximum Height	Up Travel Speed*	Tilt Speed*
24”	15”	24” x 36”	48” x 60”	39”	12.5 sec.	15 sec.
36”	15”	24” x 48”	48” x 60”	51”	20 sec.	15 sec.
48”	15”	24” x 64”	48” x 64”	63”	22.5 sec.	15 sec.

#### Standard Features:

- 2 HP, three phase motor, 230/460 volt (Optional 5 HP, 230/460 volt OR 1 HP, 120 volt )
- Control voltage, 120 volt AC
- Hand held pendant, push button control. (Optional foot pedal control)
- DU bearing, lubricated for life.
- Turned, ground, polished and hard chromed axel pins
- Captured upper and lower rollers to prevent upending.
- External power pack.
- Engineered and built in accordance with ANSI MH 29.1

**\*\*Consult factory for non-standard sizes\*\***



## Lift Table Specifications

### “LE” Series Low Entry Lift Tables 2,500 lb. Capacity

Vertical Travel	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Maximum Height	Up Travel Speed*
33”	3/8”	40” x 48”	64” x 55”	33 3/8”	10 sec.
33”	3/8”	46” x 48”	70” x 55”	33 3/8”	10 sec.
33”	3/8”	52” x 48”	76” x 55”	33 3/8”	10 sec.

### “LE” Series Low Entry Lift Tables 4,000 lb. Capacity

Vertical Travel	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Maximum Height	Up Travel Speed*
33”	3/8”	40” x 48”	64” x 55”	33 3/8”	20 sec.
33”	3/8”	46” x 48”	70” x 55”	33 3/8”	20 sec.
33”	3/8”	52” x 48”	76” x 55”	33 3/8”	20 sec.

### “LE” Series Low Entry Lift Tables 6,000 lb. Capacity

Vertical Travel	Lowered Height	Standard Table W x L	Optional Max. Size W x L	Maximum Height	Up Travel Speed*
33”	3/8”	40” x 48”	64” x 55”	33 3/8”	20 sec.
33”	3/8”	46” x 48”	70” x 55”	33 3/8”	20 sec.
33”	3/8”	52” x 48”	76” x 55”	33 3/8”	20 sec.

#### Standard Features:

- 2 HP, three phase motor, 230/460 volt (Optional 5 HP, 230/460 volt OR 1 HP, 120 volt )
- Control voltage, 120 volt AC
- Hand held pendant, push button control. (Optional foot pedal control)
- DU bearing, lubricated for life.
- Turned, ground, polished and hard chromed axel pins
- Captured upper and lower rollers to prevent upending.
- External power pack
- Engineered and built in accordance with ANSI MH 29.1

**\*\*Consult factory for non-standard sizes\*\***