

AMERICA'S ULTIMATE YARD RAMP

MOBILE YARD RAMP SPECIFICATIONS

Steel Ramps with Steel Grating

Capacity	Length	Overall Width	Usable Width	Approx. Weight	Height Range	Model Number
16,000	36'	70"	62"	5,350	38" – 65"	SYR16-70-36PL8
16,000	36'	84"	76"	5,990	38" – 65"	SYR16-84-36PL8
16,000	36'	96"	88"	6,700	38" – 65"	SYR16-96-36PL8
20,000	36'	70"	62"	5,480	38" – 65"	SYR20-70-36PL8
20,000	36'	84"	76"	6,120	38" – 65"	SYR20-84-36PL8
20,000	36'	96"	88"	6,910	38" – 65"	SYR20-96-36PL8
25,000	36'	70"	62"	6,440	38" – 65"	SYR25-70-36PL8
25,000	36'	84"	76"	7,130	38" – 65"	SYR25-84-36PL8
30,000	36'	84"	76"	7,870	38" – 65"	SYR30-84-36PL8

Aluminum Ramps with Steel Grating

Capacity	Length	Overall Width	Usable Width	Approx. Weight	Height Range	Model Number
16,000	36'	70"	62"	4,700	38" – 65"	AS16-70-36PL8
16,000	36'	84"	76"	5,600	38" – 65"	AS16-84-36PL8
20,000	36'	70"	62"	4,800	38" – 65"	AS20-70-36PL8
20,000	36'	84"	76"	5,700	38" – 65"	AS20-84-36PL8
25,000	36'	70"	62"	4,900	38" – 65"	AS25-70-36PL8
25,000	36'	84"	76"	5,920	38" – 65"	AS25-84-36PL8

Standard Features:

- ✓ Steel or Aluminum I-Beam Construction
- ✓ 7" Steel Curbs / 7" Aluminum Curbs
- ✓ 36' in Length
- ✓ 8' Level-Off
- ✓ 30" Approach Ramp
- ✓ 15" Lip
- ✓ 1 ¾" Serrated Steel Grating
- ✓ 18" Solid/Pneumatic Tires
- ✓ Single Acting Hydraulic Pump
- ✓ Positioning Sleeve (180° rotation)
- ✓ Safety Chains

Options

- ✓ Tow-Bar



by JH INDUSTRIES, INC.