

#1 YARD RAMP IN AMERICA

MOBILE YARD RAMP SPECIFICATIONS

Steel Ramps with Steel Grating

Capacity	Length	Overall Width	Usable Width	Approx. Weight	Height Range	Model Number
16,000	36'	70"	62"	5,350	38" – 65"	SYR16-70-36PL8
16,000	36'	84"	76"	5,990	38" – 65"	SYR16-84-36PL8
16,000	36'	96"	88"	6,700	38" – 65"	SYR16-96-36PL8
20,000	36'	70"	62"	5,480	38" – 65"	SYR20-70-36PL8
20,000	36'	84"	76"	6,120	38" – 65"	SYR20-84-36PL8
20,000	36'	96"	88"	6,910	38" – 65"	SYR20-96-36PL8
25,000	36'	70"	62"	6,440	38" – 65"	SYR25-70-36PL8
25,000	36'	84"	76"	7,130	38" – 65"	SYR25-84-36PL8
30,000	36'	84"	76"	7,870	38" – 65"	SYR30-84-36PL8

Aluminum Ramps with Steel Grating

Capacity	Length	Overall Width	Usable Width	Approx. Weight	Height Range	Model Number
16,000	36'	70"	62"	4,700	38" – 65"	AS16-70-36PL8
16,000	36'	84"	76"	5,600	38" – 65"	AS16-84-36PL8
20,000	36'	70"	62"	4,800	38" – 65"	AS20-70-36PL8
20,000	36'	84"	76"	5,700	38" – 65"	AS20-84-36PL8
25,000	36'	70"	62"	4,900	38" – 65"	AS25-70-36PL8
25,000	36'	84"	76"	5,920	38" – 65"	AS25-84-36PL8

Standard Features:

- ✓ Steel or Aluminum I-Beam Construction
- ✓ 7" Steel Curbs / 7" Aluminum Curbs
- ✓ 36' in Length
- ✓ 8' Level-Off
- ✓ 30" Approach Ramp
- ✓ 15" Lip
- ✓ 1 ¾" Serrated Steel Grating
- ✓ 18" Solid/Pneumatic Tires
- ✓ Single Acting Hydraulic Pump
- ✓ Positioning Sleeve (180° rotation)
- ✓ Safety Chains

Options

- ✓ Tow-Bar



by JH INDUSTRIES, INC.